

Training Range Environmental Evaluation and Characterization System (TREECS)

Environment, Energy, Security, and Sustainability Symposium and Exhibition

May 9-12, 2011
New Orleans, LA

Billy E. Johnson, PhD, PE, D.WRE

*Jeff Gerald, Zhonglong Zhang,
Mark Dortch, and Andrew Simmons*



US Army Corps of Engineers
BUILDING STRONG®



Report Documentation Page			Form Approved OMB No. 0704-0188	
<p>Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p>				
1. REPORT DATE MAY 2011	2. REPORT TYPE	3. DATES COVERED 00-00-2011 to 00-00-2011		
4. TITLE AND SUBTITLE Training Range Environmental Evaluation and Characterization System (TREECs)			5a. CONTRACT NUMBER	
			5b. GRANT NUMBER	
			5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)			5d. PROJECT NUMBER	
			5e. TASK NUMBER	
			5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Army Engineer Research and Development Center, Construction Engineering Research Laboratory, PO Box 9005, Champaign, IL, 61826-9005			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)	
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited				
13. SUPPLEMENTARY NOTES Presented at the NDIA Environment, Energy Security & Sustainability (E2S2) Symposium & Exhibition held 9-12 May 2011 in New Orleans, LA.				
14. ABSTRACT				
15. SUBJECT TERMS				
16. SECURITY CLASSIFICATION OF: a. REPORT b. ABSTRACT c. THIS PAGE unclassified unclassified unclassified			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 30
				19a. NAME OF RESPONSIBLE PERSON

TREECS Problem Statement

- Residues and disturbances from range operations can impact the environment, including human and ecological health. Such impacts can impact environmental compliance and range sustainment.
- Army live fire training and test ranges have unique environments in which low-order and unexploded ordnance (dud munitions) are likely to cause random and highly uncertain sources of MC contamination.
- ***An assessment tool is needed to forecast if, when, and at what level MC concentrations in off-range media (groundwater, surface water, and sediment) may exceed protective health benchmarks.***



TREECS Solution / Approach

Training Range Environmental Evaluation and Characterization System (TREECS) is a client-based system that provides forecasts of Munitions Constituents (MC) fate on and off range based on munitions use on range.

Development Approach:

Formulate and couple screening level MC fate/transport-transformation-sequestration models in an integrated framework for fast assessments with a minimal amount of user input.

Partners:

PNNL, AEC, CHPPM, ITL, and EL

<http://el.erdc.usace.army.mil/treecs/>



TREECS Components

- Framework for Tier 1 and 2 assessments
- Constituent databases
- Health Benchmark database
- Munitions database
- MC residual mass loading module based on munitions use
- GIS module
- Hydro-geo-characteristics toolkit (HGCT) for estimating input parameters
- Models for soil, surface water, vadose zone, and groundwater
- Simplified user input interfaces for models (GUIs)
- Viewers for results
- Sensitivity and uncertainty module for Tier 2 assessments



TREECS Main Screen

TREECS - Training Range Environmental Evaluation and Characterization System

File References Web Data Tools Websites Options Help

Installation/AOI Description Tier Analysis Selection Site Conditions DoD Target Health Benchmarks Inputs Execute Uncertainty View Results

Installation name: Fort Benning, GA


Select Installation

Installation description:


AOI name: MyAoi

Select existing AOI

AOI description:



*Shapefiles, Grids,
and Images*



GIS
Module

Help



BUILDING STRONG®

GIS Functions/Tools



- For opening individual GIS files



- For saving individual GIS files



- For resampling a grid



- For zooming into an area in the workspace



- For zooming out of an area in the workspace



- For panning in the workspace



- For creating a rectangular AOI shapefile in the workspace



- For creating a polygon AOI shapefile in the workspace



- For measuring length and area in the workspace



- For converting a shapefile to a grid



- For extracting a subset of a grid



- For creating slope grid from DEM and performing simple arithmetic operations on a grid



Hydro-Geo-Characteristics Toolkit (HGCT)

- To aid the user in determining input variables required by TREECS models
 - ▶ Soil Properties
 - ▶ Soil erosion rate
 - ▶ Hydrology (infiltration, runoff, ET, etc.)
 - ▶ Darcy velocity
- Allows *point* (single value) and *spatially- varying* composite estimates
- Spatial option requires use of GIS module in TREECS or externally developed map files (grids)




Tiered Approach

- Tier 1 (screening)
 - ▶ Steady-state, no degradation, worse case, highly conservative
 - ▶ Requires little data
 - ▶ Can be applied very quickly
 - ▶ Indicates whether a problem could ever potentially exist; if so, proceed to Tier 2
- Tier 2 (more comprehensive)
 - ▶ Time-varying, much more realistic and accurate
 - ▶ Requires more data
 - ▶ Requires more time to set up and apply, but still can be done relatively quickly
 - ▶ Can be used to determine when benchmark exceedence may occur
 - ▶ Useful for evaluating range management strategies



Tier 1 Conceptual Model



Tier 1 Model Primary Assumptions

- Area of Interest (AOI) is homogeneous
- Constant loading of MC into impact area (could possibly add firing points later)
- Soil concentrations are at steady-state
- No decay/degradation or volatilization, except for surface water volatilization
- No losses between the AOI and receiving surface water



Tier 1 Modules

- MC mass loading based on munitions use
- Constituent databases
- Benchmark database
- Hydro-geo-characteristics toolkit (HGCT) for estimating input parameters (covered in separate session)
- GIS module for viewing of spatial info and for use in developing gridded info for HGCT spatial (covered in separate session)
- Steady-state soil model
- MEPAS Aquifer model with inputs simplified for Tier 1
- RECOVERY surface water model with inputs simplified for Tier 1
- Viewers for results



Constituent Database Module (Constituent Selection)

- Available Databases
 - ▶ FRAMES
 - ▶ Risk Assessment Information System (RAIS)
 - ▶ Army Range Constituent Database
 - ▶ User Defined (build from Con DB editor tool starting with a copy of the FRAMES (FUI) DB)
- For selecting MC and their properties
- Contains physical/chemical properties for MC and other contaminants
- Can change property values within the TREECS application, but it does not change database value



Constituent Selection

TREECS - Training Range Environmental Evaluation and Characterization System (T1APH_SP.trp)

File References Web Data Tools Websites Options Help

Installation/AOI Description Tier Analysis Selection Site Conditions DoD Target Health Benchmarks Inputs Execute Uncertainty View Results

Constituent Selection Operational Inputs

Select Database

Select the constituent database to use:

- FRAMES Constituent Database
- Army Range Constituent Database
- Risk Assessment Information System (RAIS)
- User Defined Constituent Database

Can use a user defined database (Create under Tools)

Select MC

Available constituents (CASRN):

- 1,1 dichloroethylene (75354)
- vinylidene chloride (75354)
- 1,1,1,2-tetrachloroethane (630206)
- 1,1,1-trichloroethane (71556)
- methyl chloroform (71556)
- 1,1,2,2-tetrachloroethane (79345)

Search: Find /Find Next... List by CASRN (name)

Currently selected constituents (CASRN):

- rdx (121824)
- tnt (118967)
- lead (7439921)
- copper (7440508)
- potassium perchlorate (7778747)

View MC Properties

Remove Info

®

MC Residue Mass Loading Module (Operational Inputs)

TREECS - Training Range Environmental Evaluation and Characterization System (T1APH_SP.trp)

File References Web Data Tools Websites Options Help

Installation/AOI Description Tier Analysis Selection Site Conditions DoD Target Health Benchmarks Inputs Execute Uncertainty View Results

Constituent Selection Operational Inputs

Type of loading to be estimated:

- Impact Zone
- Firing Point

Select the munitions database to use:

- Default munitions database
- User defined munitions database

User defined munitions database: C:\Program Files\TREECS\Data

Munitions master list:

- AP Hill B584 (NSN: 0001) (DODIC: B584)
- AP Hill L601 (NSN: 0002) (DODIC: L601)
- AP Hill L594 (NSN: 0003) (DODIC: L594)
- AP Hill H975 (NSN: 0004) (DODIC: H975)
- AP Hill D544 (NSN: 0005) (DODIC: D544)

Search:

Munitions used at this site/range:

- AP Hill D544 (NSN: 0005) (DODIC: D544)
- AP Hill B546 (NSN: 0007) (DODIC: B546)
- AP Hill B470 (NSN: 0008) (DODIC: B470)
- AP Hill B542 (NSN: 0009) (DODIC: B542)
- AP Hill B103 (NSN: 0010) (DODIC: B103)

Remove

Munitions usage information:

Munition: AP Hill D544 (NSN: 0005) (DODIC: D544)

Starting year of simulation:

Rounds fired per year: 861

Dud percentage: 0

Low order percentage: 2

High order percentage: 98

Percentage of duds sympathetically detonated: 0

Sympathetic dud yield percentage: 100

Low order yield percentage: 50

High order yield percentage: 100

Help

Constant in Tier 1

Pulled from MIDAS Extract DB

Provided by user

Constituent masses are summed across PEP, bulk, and inert material types and used as the total mass available at the impact or firing point. It is assumed that the fraction of summed constituent mass consumed in the yield is vaporized and is not available as residue.




MC Residue Mass Loading

$$L_{i,k} = \sum_{j=1}^{j=n} \left\{ N_{j,k} M_{i,j} \left[\frac{LO_{j,k} (100 - Y_{Loj,k}) + HO_{j,k} (100 - Y_{Hoj,k}) + DUD_{j,k} SYM_{j,k} (100 - Y_{Symj,k})}{100} \right] \right\}$$

$L_{i,k}$	= Loading for constituent I for year k, g/yr
$DUD_{j,k}$	= percent of duds for munitions item j for year k
$HO_{j,k}$	= percent of high order detonations for munitions item j for year k
$LO_{j,k}$	= percent of low order detonations for munitions item j for year k
$M_{i,j}$	= mass of constituent i in munitions item j delivered to impact area, g/item
$N_{j,k}$	= number of munitions item j fired for year k
n	= total number of munitions items used at AOI
$SYM_{j,k}$	= percent of sympathetic detonation of duds for munitions item j for year k
$Y_{Hoj,k}$	= percent yield of munitions item j due to high order detonation for year k
$Y_{Loj,k}$	= percent yield of munitions item j due to low order detonation for year k
$Y_{Symj,k}$	= percent yield of munitions item j due to sympathetic detonation for year k



DoD Protective Health Benchmarks

Database Construct

- Media and end point
 - ▶ Soil: human and eco (grayed out since no values currently)
 - ▶ Groundwater: human
 - ▶ Surface water: eco and human
 - ▶ Surface water sediments: eco



Benchmark Database Module

TREECS - Training Range Environmental Evaluation and Characterization System (T1APH_SP.trp)

File References Web Data Tools Websites Options Help

Installation/AOI Description Tier Analysis Selection Site Conditions DoD Target Health Benchmarks Inputs Execute Uncertainty View Results

Select from the benchmark options below:

DoD Target Health Benchmarks 

User-defined benchmark database 

Can use the DoD DB or a User Defined DB

	Constituent Name	Constituent CASRN	Media	Receptor	Value	Unit
▶	RDX	121-82-4	surfacewater-marine	Eco	5000	ug/L
	RDX	121-82-4	sediment-marine	Eco	0.026	mg/kg
	RDX	121-82-4	surfacewater-fresh	Eco	190	ug/L
	RDX	121-82-4	sediment-fresh	Eco	0.026	mg/kg
	RDX	121-82-4	surfacewater-fresh	Human	0.61	ug/L
	RDX	121-82-4	0.01	"


Ecological Surface Water/Sediment is marine (as opposed to freshwater) 

Sediment TOC: .02 fraction 


Soil TOC: fraction



Tier 1 Soil Model



Aquifer Model for Tier 1 – MEPAS Aquifer with less inputs (prescribed inputs)




Conceptual Model

Don't need to model vadose zone for steady-state

AOI length and width are input in Soil MUI


MEPAS coordinates



Single Well Location




Tier 1 Surface Water Model (*RECOVERY* with fewer inputs – prescribed inputs)




Model conceptualization

MC runoff/erosion
dumps directly into
surface water, i.e., no
routing or in-path
storage



Tier 2 Conceptual Model



Tier 2 Model Primary Assumptions

- Area of Interest (AOI) is homogeneous
- Inputs and model responses are time-varying
- There can be fate losses, such as degradation (1st order)
- Sorption is linear, reversible equilibrium
- Solid and non-solid phase mass are tracked with dissolution
- No losses between the AOI and receiving surface water for runoff/erosion and interflow
- Steady-state hydrologic inputs (average annual conditions) like Tier 1
- Vadose transport is 1D vertical




Tier 2 Modules


- Same as Tier 1 except for the following additions:
 - ▶ Tier 2 soil model is used instead of Tier 1 soil model
 - ▶ MEPAS Vadose Zone model and flux viewer
 - ▶ Contaminant Model for Streams (CMS); user must choose whether to use CMS or RECOVERY for surface water and sediments (default is RECOVERY)
 - ▶ Sensitivity and Uncertainty (S/U) based on Monte Carlo simulation with Latin Hypercube sampling
 - ▶ S/U viewers
 - ▶ Plus-SG Operator: allows aquifer discharge to surface water; transparent to user other than having to specify the aquifer discharge rate to surface water



Tier 2 Soil Model




MEPAS Vadose & Aquifer Models for Tier 2 with full Capabilities




Vadose Zone included

AOI length and width are input in Soil MUI


MEPAS coordinates



Tier 2 Surface Water Models, RECOVERY and CMS with full Capabilities



RECOVERY Model conceptualization



CMS conceptualization



Sensitivity/Uncertainty Module


- Declare uncertain parameters
- Declare variables and their features to watch for output, e.g., aquifer concentration at specific years or peak concentration for simulation
- Specify the type of distribution and its statistics for each uncertain parameter, e.g., normal distribution with mean, upper and lower bounds, and standard deviation
- Set random seed and number of Monte Carlo iterations




S/U Example Output Viewer

Concentration versus time
with confidence limits

Aquifer to well 1:exp20 Bounding Bars Constituent Concentration for Cadmium (7440439)



Sediment to Lake 1:exp26 Bound Bars Constituent Concentration for Cadmium (7440439)



TREECS Status

- Currently being tested and validated using existing training range data by EL, AEC, and CHPPM personnel
- Used to help support ORAP Phase II Assessments
- FY11-FY13 – Further enhancements to Tier 1 and Tier 2 modeling capabilities and database expansions
- FY11-FY13 – Development and Implementation of a Fully Explicit Physically Based Watershed Modeling capability within the TREECS Framework – *Useful for evaluating mitigation scenarios for multiple AOIs covering complex terrain*



Questions?



<http://el.erdc.usace.army.mil/treecs/>

Billy E. Johnson
601-634-3714
Billy.E.Johnson@usace.army.mil



BUILDING STRONG®